

SINGLE TOGGLE JAW CRUSHER

CAPACITY

German Technolog

20 - 500 TPH

· APOLLO

¥.

Innovative Design, Technology & Service

www.apollo.co.in

SINGLE TOGGLE JAW CRUSHER

CAPACITY

20 – 500 TPH

Apollo Jaw crushers are built with the help of state of art CNC machines. Stringent quality control process ensures that the products are delivered ready to run and trouble free. The jaw Crusher by Apollo evolved from world famous GERMAN TECHNOLOGY and is best in the class in terms of productivity & reliability. Single toggle jaw crushers are designed to impart on a rock particle placed between a fixed and moving jaw plate. The moving jaw plate applies the force of impact on particles held against the fix jaw plate. Both the jaw plates are bolted on to heavy block. The moving jaw plate is pivoted at the top end and connected to an eccentric shaft. The retrieving action of the jaw plate travel is done by spring pulling system.

Features

- ✓ Welded and stress relieved heavy duty frame.
- Equipped with heavy duty spherical roller bearings.
- Large diameter drop forged eccentric drive shaft.
- Long crushing chamber with flywheel to ensure high inertia to crush even the hardest materials.
- High operational reliability.
- Easy replacement of wear and spare parts.
- ✓ Low operating and maintenance cost.
- ✓ Built as mobile, semi-mobile and stationary installation.
- ✓ Hydraulics aided gap adjustment for jaw setting.

Specifications

Model	Capacity (tph)	Max. Feed Size (mm)	Closed Side Setting (mm)	Crusher Speed (rpm)	Power Rating (kW)	Weight (ton)
B 500 x 300	16 - 50	250	20 - 60	300	22	4.2
B 600 x 300	20 - 60	250	20 - 60	300	30	4.6
B 600 x 400	30 - 70	350	30 - 80	300	37.5	4.7
B 900 x 600	100 - 180	500	60 - 150	300	75	12.5
B 1050 x 750	120 - 250	600	80 - 180	230	110	22.5
B 1250 x 900	200 - 450	750	90 - 210	220	150	34
B 1300 x 1100	250 - 500	1000	110 - 300	220	250	40
B 1200 x 250	30 - 75	200	10 - 75	300	45 - 55	11



Crawler Mounted

Wheel Mounted

Skid Mounted

With Apollo's policy of constant upgradation of products, specifications are subject to change without prior notice. Accessories shown are optional and not a part of standard supply. Technical data are approximate and should be used as a guide only. Capacity and power requirements depend on the type and characteristics of the feed materials.



GUJARAT APOLLO INDUSTRIES LIMITED

Corporate Office : "Parishram" 5-B, Rashmi Society, Near Mithakhali Circle, Navrangpura, Ahmedabad - 380009, India. +91-79-2644 4597 / 2656 4705

Regd. Office & Works : Block No. 486, 487, 488, Dholasan, Dist.: Mehsana - 382732 (Gujarat) India.

marg 10/2020